



SPI-14/18-2150

400 MHz to 2150 MHz, Satellite In-Line Power Inserter



Features

- TruSpec power inserters supply constant DC voltage to C/Ku or DSS satellite LNBS, microwave down converters, and in-line amplifiers
- Plug-in external UL power wall adapter included
- Input voltage of 100 to 240 V, 50 Hz, 60 Hz
- Operating frequency from 400 MHz to 2150 MHz
- Two Independent paths
- Output voltage selection switch from 13 VDC to 14/17 VDC to 18 VDC or 17 VDC to 18/17 VDC to 18 VDC, 1,000 mA
- Insertion loss of 2 dB ± 1 dB
- Isolation of 65 dB
- UL-approved external universal AC power adapter for domestic and international use



Power Adapter

Specification

Bandwidth	400 MHz to 2150 MHz
Insertion Loss	2 dB
Isolation	65 dB
Input Connector	75 Ω, F-female
Output Connector	75 Ω, F-male
Input Voltage	100 to 240 V, 50 Hz, 60 Hz
Output Voltage Port 1	18 VDC
Output Voltage Port 2	14 VDC / 18 VDC sw.
LNB Current Each Path	1,000 mA

Ordering Information

SPI-14/18-2150 400 MHz to 2150 MHz Satellite In-Line Power Inserter

