PRIMEX TELECOM

Product Specification Sheet

Verge P3000

Media Distribution Enclosure

1. PRODUCT SUMMARY

The Primex Verge P3000 WiFi transparent Media Distribution Enclosure for structured wiring brings reliability when managing today's inside cable system requirements. Its flexible design provides a convenient, lockable and centralized location for easy installation and distribution of multi-play services within residential and commercial premises.

2. PRODUCT DIMENSIONS

Inside H 30"/W: 14"/D: 3.5"

3. FEATURES & BENEFITS

- One convenient and centralized location for easy installation and distribution of multi-play services.
- WiFi transparent plastic delivers up to 15 times more wireless signal strength than metal alternatives.
- Eliminate interference with equipment such as a router's wireless signal with ABS polymer construction.
- Easy installation and transportation with the lightweight design.
- Easier cable routing and entry with twelve 1" entry/ exit ports and two 1/4" knockouts.
- Increase flexibility of installation with a mounting hole pattern.
- Secured via dual key locks: P/N:125-1064
- Assure safety and durability with UL safety standard compliant flame retardant polymer.
- These enclosures should not be installed in a fire rated wall as they are not fire rated.

4. CONFIGURATIONS

 SC
 Description

 125-0990
 P3000K Base/Lid/Frame (lockable)

 125-1197
 P3000KKITHOUST (w/pins, clips, UMP)

 125-0992
 P3000K Lid & Frame (non-lockable)



