

PRODUCT SPECIFICATIONS			
		SPECIFICATIONS	
		Connector Type	RJ45 Waterproof Connector
			Female to Female CAT6 Shielded
		Core	8CORES
		Rating	UL94V-0
		Cable Compatibility	CAT6
		Cable OD:	3 ~ 8 mm
		Transfer Speed	10BASE-T, 100BASE-T, 1000BASE-T, 10000BASE-T
		Electrical Current Rate	1.5 Amps
		Voltage Rate	125VAC, 75VDC
		Insulation Resistance	> 500MΩ
AT-A-GLANCE		Withstanding Voltage	AC1000V 50HZ or 60HZ 1 Minute
CONNECTOR TYPE	CAT6 Outdoor Shielded	Contact Resistance	<10MΩ
	Waterproof Coupler	Insert Force	900g
PACKAGING	Polybag	Cooperate Strength: Plug & Socket	7.7 kg
AVAILABLE QUANTITIES	Sold Individually	Lifetime	> 750 times
COMPATIBILITY & COMPLIANCE		Housing	Nylon PA66 (UL94V-0)
		Contact Needle OD / Material	0.5 mm, Phosphorous Copper
ROHS compliant	Rated	Shield Cover	Nickel Plated Over 0.25 mm Copper Alloy
compliant	IP68	Contact Needle	Gold-Plated 6U"
		Waterproof Ring	Silica Gel
		Working Temperature	-40°C ~ 120°C
VERICOM <sup>®</sup> CAT6 Outdoor Shielded Waterproof Coupler		Storage Temperature	-25°C ~ 85°C
		Atmospheric Pressure	86 ~ 106Kpa
The Vericom CAT6 RJ45 Shielded Female Waterproof Connector is designed to connect two CAT6 shielded patch cords together, leaving a watertight connection rated to an IP68 industrial standard. It is ideal for harsh industrial or outdoor environments.		Humidity	≤ 90%
		FEATURES & BENEFITS	
		<ul> <li>PCB, 8U" gold plated for better contact at higher speeds</li> <li>Compact Size, Sleek, Professional Appearance</li> <li>PA66 Nylon is anti-flame and anti-UV for longevity</li> <li>Blue sealing ring up to IP68 in 1 meter depth</li> <li>Solid body made by injection &amp; cold compression</li> <li>Rubber ring for an added moisture barrier</li> <li>Shielded to prevent signal interference</li> </ul>	
		PART NUMBER	QUANTITY
		MCP6S-04683	Sold Individually


TECHNICAL SHEETS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Rev.20161003.1

© 2015 VERICOM Global Solutions

p 865.671.4455 · f 865.671.4497 · 10025 Investment Drive, Suite 120 Knoxville TN 37932 info@vericomsolutions.com · www.vericomsolutions.com





© 2015 VERICOM Global Solutions

p 865.671.4455 · f 865.671.4497 · 10025 Investment Drive, Suite 120 Knoxville TN 37932 info@vericomsolutions.com · www.vericomsolutions.com